Viper 20T/HD How To Prepare for use							
1 Unplug battery charger.	2 <i>Ever recovery tank lid.</i>	3 Inspect ball float cage.					
4 Fill solution tank with water (do not exceed 130°F).	5 Fill solution tank with water (do not exceed 130°F).	6 Inspect squeegee blade and install squeegee.					
7 Inspect brush or pad.	8 Install brush or pad-holder under the deck.	9 Turn on brush/pad- holder switch.					
10 Press handle button to engage brush. Repeat this step if necessary.	11 Choose solution flow for the type of work to be performed.	12 Lower squeegee lever.					





	Viper 20T/HD How To								
Store the Machine									
1	Empty recovery tank and solution tank.	2	Wash recovery tank and vacuum grid with clean water.	3	Inspect and clean, cover gasket, vacuum grid and automatic shut-off float.				
4	Inspect hoses; replace if kinked or damaged.	5	Remove, rinse and inspect squeegee. Replace if needed.	6	Remove, clean and inspect brush or pad. Rinse with warm water. Hang to dry. Replace if needed.				
7	Lift recovery tank lid.	8	Charge batteries.	9	Plug machine up to charge for next use.				





Viper 20T/HD How To								
Weekly Maintenance								
1	Perform a squeegee blade check.	2	Inspect and clean solution filter.	3	Check each battery cell's water level (does not apply to gel batteries).			
	Six Month Maintenance		Yearly Maintenance		Yearly Maintenance			
4	Perform a screw and nut tightening check	5	Brush/pad-holder motor carbon brush check or replacement	6	Vacuum system motor carbon brush check or replacement			



